

## Couplings according British Standard BS 336


A non-symmetrical quick connection coupling with a male and female part. These couplings are only suitable for delivery operation. For suction operation round thread couplings are in use.

- Aluminium alloys (A)
- Copper alloys (C)

### Delivery hose couplings Instantaneous



1010



1010

Nominal size (inch)	For hose i. d. inch (mm)	Weight (kg)	Ident.No.	Remarks	Alloy
1 1/2"	1 1/2" (38)	0,410	30227632	multi-serrated	A
1 1/2"	1 1/2" (38)	1,380	30227693	multi-serrated	A
2 1/2"	1 1/2" (38)	0,950	30226232		A
2 1/2"	1 1/2" (38)	2,750	40339495		A
2 1/2"	1 3/4" (45)	1,000	30245233		A
2 1/2"	1 3/4" (45)	2,800	40074993		A
2 1/2"	2" (52)	0,960	30204433		A
2 1/2"	2" (52)	2,800	40098193		A
2 1/2"	2 1/2" (64)	0,980	30203733		A
2 1/2"	2 1/2" (64)	2,800	40144693		A
2 1/2"	2 3/4" (70)	1,050	30053633		A
2 1/2"	2 3/4" (70)	2,800	40077893		A
2 1/2"	3" (75)	1,100	60654333		A

As per: 23.03.2010